BODY 900 CAVITY WAX SPRAY

Technical Data Sheet No 829

VOC compliant with the regulations

A combination of caoutchouc/ synthetic resin which has excellent anticorrosive properties

For the interior and recessed parts of a car body, the inside of the doors, and engine compartment and the headlight interiors

Remains permanently elastic

Fast drying

General Technical Description

2-3 passes

Dust free 10 min at 23°C

Surface

Inside bottom parts of the car body

Outside bottom parts of the car body

Pretreatment / Cleaning of substrate

Clean substrate using a soft cloth and BODY 770 ANTISIL NORMAL / BODY 771 ANTISIL FAST

Make sure the surface is air dried rather than wiped dry

Make sure you always use appropriate face protection and good ventilation

Product Application: »» Apply on the inside and outside bottom parts of the car body.

Shake well before using

2-3 coats approximately 20-30 microns

Spray at a distance of 20-30 cm thinly applied coats build up within 5-10 min intervals to achieve best results.

Dust free 10 min at 23°C

Flash Point:
-97°C

Specific Gravity:
0.7 g/cm ^{3}

Solid Content (No thinner):
22 % Weight

VOC (2004/42/EC)

This is an aerosol product based on its ingredients and its properties. The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 400g/L.
2004/42/IIB(e)(840)400

Theoretical Coverage:
-

Cleaning of equipment:
-

Remarks:
- Always try to use the product in accordance with the specifications provided.
- It can be used by countries that do not adopt the VOC legislation as well.
- Shake thoroughly before use.
- Shake for 2-3 min after agitator ball has started to rattle.

After preparing the area to be painted ensure it to be free from dirt, wax, oil etc. Test on a similar surface using a back and forth action.
- Optimum operating temperature range 10-25 °C.

Shelf life:
- Up to 36 months unused spray.
- +5 to +25 °C

Issue 3 / 2015, September 2015