



803 FLEX AGENT

Technical Data Sheet No 903

Additive for improving the flexibility of paint for parts made of plastic (e.g. bumpers, spoiler, etc.).

General Technical Description

Special additive for flexing of 2K products

Specially formulated highly flexible resin mixture.

Easy to use

Surface

Mainly plastic parts of the car

Pretreatment / Cleaning of substrate



Clean substrate using a soft cloth and 770 ANTISIL NORMAL / 771 ANTISIL FAST DEGREASER

Make sure the surface is first wiped dry then air dried



Make sure you always use appropriate face protection and good ventilation

Product Application:

»»» Before use, shake the contents of 803 FLEX AGENT can, well. Add 5% on part A of 2K primers and 10-15% on part A of 2K clears respectively, and then mix in the hardener and the thinner. Scrub the plastic surface, on which paint is to be applied, lightly using Scotch Brite (or something similar), and then clean with 770 ANTISIL NORMAL / 771 ANTISIL FAST DEGREASER. Apply BODY PAINT/ADDITIVE mixture with a spray gun. Follow the product application of the 2K primer or 2K top coat.



Always wear protective equipment



Follow the application instructions mentioned in this TDS

Flash Point:
23°C

Specific Gravity:
0.94 g/cm³

Solid Content (No thinner):
35% Weight

VOC (2004/42/EC)
-

Theoretical Coverage:
-

Cleaning of equipment:
Clean after final use with 740 ACRYL NORMAL THINNER / REDUCER

Remarks:

- Best results when used with HB BODY PRODUCTS
- It can be used by countries that do not adopt the VOC legislation as well.

Storage shelf life:

- Store in a cool place +5 to +25°C (+41°F to +77°F) and use within 12 months for best results. Guaranteed shelf life of 24 months in unused original containers.

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.