

Safety data sheet according to 1907/2006/EC, Article 31

- SECTION 1: Identification of the substance/mixture and of the company/undertaking
- 1.1 Product identifier
- Trade name: BODY AUTOCLEAR 493 2:1 MAT CLEAR CM-HS
- · Article number: 431
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC3 Air care products
- Process category PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
- Environmental release category ERC2 Formulation into mixture
- · Article category AC1 Vehicles
- · Application of the substance / the mixture Surface protection
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI.GREECE

Ph: +30 2310 790 000 Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

Further information obtainable from:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022. SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

· 1.4 Emergency telephone number:

Regional Medicines and Poisons Information Centre NI

Pharmacy Department, Royal Hospital Suite

Grosvenor Road Belfast

Telephone: +44 28 90 63 2032

Fax: +44 28 90 24 80 30

Emergency telephone: 844 892 0111

E-mail address: nirdic.nirdic@belfasttrust.hscni.net

Trade name: BODY AUTOCLEAR 493 2:1 MAT CLEAR CM-HS

(Contd. of page 1)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02

GHS07

- · Signal word Warning
- Hazard-determining components of labelling:

n-butyl acetate

1-methoxy-2-propanol

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray. P261

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

Store locked up. P405

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Additional information:

EUH208 Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate. May produce an allergic reaction.

- · 2.3 Other hazards
- Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- **Description:** Mixture of hazardous substances

(Contd. on page 3)

Trade name: BODY AUTOCLEAR 493 2:1 MAT CLEAR CM-HS

n-butyl acetate

Flam. Liq. 3, H226

2-butoxyethyl acetate

1-methoxy-2-propanol

• Flam. Liq. 3, H226

Acute Tox. 3, H331 **STOT SE 3, H336**

Flam. Lig. 3, H226

1 Acute Tox. 4, H312; Acute Tox. 4, H332

(1) STOT SE 3, H336

(Contd. of page 2)

25-<30%

10-<15%

5-<10%

5-<10%

≥0.1-<0.25%

Dangerous components:

CAS: 123-86-4 EINECS: 204-658-1

Index number: 607-025-00-1

RTFCS: AF 7350000

Reg.nr.: 01-2119485493-29-007 01-2119485493-29-004

> 01-2119485493-29-003 01-2119485493-29-005

01-2119485493-29

CAS: 112-07-2

EINECS: 203-933-3 Index number: 607-038-00-2

RTECS: KJ 8925000

Reg.nr.: 01-2119475112-47-0002

CAS: 107-98-2 EINECS: 203-539-1

Index number: 603-064-00-3 RTECS: UB 7700000

CAS: 1330-20-7

EINECS: 215-535-7 Index number: 601-022-00-9

RTECS: ZE 2100000

Reg.nr.: 01-2119488216-32-001 01-2119488216-32-002 01-2119488216-32-003

CAS: 41556-26-7

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate EINECS: 255-437-1 Aguatic Acute 1, H400; Aquatic Chronic 1, H410

xvlene

Skin Sens. 1, H317

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact:

Immediately rinse with water.

In case of skin contact DO NOT clean effected area with solvents or thinners. Take off all contaminated clothing at once. Wash skin thoroughly with neutral pH soap and water. In any suspicion that skin irritation persists call a doctor.

- · **After eye contact:** Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Page 4/15

Safety data sheet

according to 1907/2006/EC. Article 31

Printing date 25.04.2020 Revision: 25.04.2020 Version number 17

Trade name: BODY AUTOCLEAR 493 2:1 MAT CLEAR CM-HS

(Contd. of page 3)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- **Suitable extinguishing agents:** CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

Speial protective equipment and fire fighting procedures:

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

· **Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

Observe label precautions. Store between 5 and 25 degrees Celcius in a dry, well ventilated place away from sources of heat, ignition and

direct sunlight. No smoking, Prevent access from unauthorised personell, Containers which are opened must be carefully resealed and

upright to prevent leakage. The storage and use of this product is subject to the requirements of the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). Up to 250 litres of such flammable liquids may be stored in a work area provided they are kept in a fire-proof cupboard or bin. Larger quantities must be kept in a separate storeroom conforming to the structural requirements of the regulations. Further guidance is contained in the HSE ACOP L135, "Storage of Dangerous Substances." UK.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

Trade name: BODY AUTOCLEAR 493 2:1 MAT CLEAR CM-HS

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

112-07-2 2-butoxyethyl acetate

WEL Short-term value: 332 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm Sk

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk: BMGV

· Regulatory information WEL: EH40/2020

Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Revision: 25.04.2020 Version number 17

Trade name: BODY AUTOCLEAR 493 2:1 MAT CLEAR CM-HS

(Contd. of page 5)

For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

The breakthough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the baseis of the different substances in the preparation.

- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- · For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Rubber gloves
- Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- General Information
- Appearance:

Form: Liquid
Colour: Whitish
Odour: Characteristic
Odour threshold: Not determined.

PH-value: Not determined.

Change in condition

Melting point/freezing point:
Initial boiling point and boiling range:Undetermined.120.3 °CFlash point:23 - 60 °CFlammability (solid, gas):Not applicable.

· Autoignition temperature: 270 °C

• **Decomposition temperature:** Not determined.

• Auto-ignition temperature: Product is not selfigniting.

• **Explosive properties:** Risk of explosion by shock, friction, fire or other sources of ignition.

Explosion limits:

Lower: 1.2 Vol %
Upper: 8.4 Vol %

Vapour pressure at 20 °C: 10.7 hPa

Density at 20 °C: 1.06 g/cm³

Relative density Not determined.

Vapour density Not determined.

Evaporation rate Not determined.

Solubility in / Miscibility with

water: Fully miscible.

· Partition coefficient: n-octanol/water: Not determined.

Trade name: BODY AUTOCLEAR 493 2:1 MAT CLEAR CM-HS

(Contd. of page 6)

Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

Solvent content:

 Organic solvents:
 50.8 %

 VOC (EC)
 538.8 g/l

 Solids content (volume):
 48.9 %

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Dermal LD50 10.368 mg/kg (rabbit)

Inhalative LC50/4 h 40.9 mg/l

123-86-4 n-butvl acetate

Oral LD50 13,100 mg/kg (rat)
Dermal LD50 >5,000 mg/kg (rabbit)

Inhalative LC50/4 h >21 mg/l (rat)

112-07-2 2-butoxyethyl acetate

 Oral
 LD50
 2,400 mg/kg (rat)

 Dermal
 LD50
 1,580 mg/kg (rabbit)

Inhalative LC50/4 h 11 mg/l (ATE)

107-98-2 1-methoxy-2-propanol

Oral LD50 5,660 mg/kg (rat)
Dermal LD50 13,000 mg/kg (rabbit)

Inhalative LC50/4 h 6 mg/l (rat)

7631-86-9 silicon dioxide, chemically prepared

Oral LD50 10,000 mg/kg (rat)

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)
Dermal LD50 2,000 mg/kg (rabbit)
Inhalative LC50/4 h 11 mg/l (ATE)

according to 1907/2006/EC, Article 31

Printing date 25.04.2020 Revision: 25.04.2020 Version number 17

Trade name: BODY AUTOCLEAR 493 2:1 MAT CLEAR CM-HS

(Contd. of page 7)

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

· 12.2 Persistence and degradability

This prouduct contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic(PBT).
- · **VPvB:** This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- European waste catalogue

HP3 Flammable

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

- Uncleaned packaging:
- · **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

Page 9/15 according to 1907/2006/EC, Article 31

Printing date 25.04.2020 Revision: 25.04.2020 Version number 17

Trade name: BODY AUTOCLEAR 493 2:1 MAT CLEAR CM-HS

(Contd. of page 8)

Safety data sheet

SECTION 14: Transport information

· 14.1 UN-Number

ADR, IMDG, IATA UN1263

14.2 UN proper shipping name

· ADR **UN1263 PAINT**

IMDG, IATA **PAINT**

· 14.3 Transport hazard class(es)

ADR



Class 3 (F1) Flammable liquids.

Label

IMDG, IATA



· Class 3 Flammable liquids.

·Label 3

· 14.4 Packing group

ADR, IMDG, IATA Ш

· 14.5 Environmental hazards:

Marine pollutant:

· 14.6 Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): · EMS Number: F-E,S-E Stowage Category Α

· 14.7 Transport in bulk according to Annex II of Marpol

and the IBC Code Not applicable.

Transport/Additional information:

· ADR

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

Transport category 3 Tunnel restriction code D/E

· IMDG

· Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation": UN 1263 PAINT, 3, III

Trade name: BODY AUTOCLEAR 493 2:1 MAT CLEAR CM-HS

(Contd. of page 9)

SECTION 15: Regulatory information

•3Y

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02

GHS07

· Signal word Warning

· Hazard-determining components of labelling:

n-butyl acetate

1-methoxy-2-propanol

· Hazard statements

H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Department issuing SDS: Department of Quality Control

Page 11/15
Printing date 25.04.2020

Safety data sheet according to 1907/2006/EC, Article 31

Trade name: BODY AUTOCLEAR 493 2:1 MAT CLEAR CM-HS

(Contd. of page 10)

Contact:

Revision: 25.04.2020 Version number 17

HB BODY S.A

Ms Olympia Stamkou Ph: +30 2310 790 032 fax: +30 2310 790 033

email: stamkou@hbbody.com

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - dermal - Category 4

Acute Tox. 3: Acute toxicity - inhalation - Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

* Data compared to the previous version altered.

GB

(Contd. on page 12)

according to 1907/2006/EC, Article 31

Printing date 25.04.2020 Revision: 25.04.2020 Version number 17

Trade name: BODY AUTOCLEAR 493 2:1 MAT CLEAR CM-HS

(Contd. of page 11)

Annex: Exposure scenario 1

- · Short title of the exposure scenario
- **Sector of Use** SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- · **Product category** PC3 Air care products
- Process category PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
- · Article category AC1 Vehicles
- Environmental release category ERC2 Formulation into mixture
- Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

Conditions of use According to directions for use.

Duration and frequency

5 workdays/week.

Frequency of use:

· Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Used amount per time or activity Smaller than 100 g per application.
- Other operational conditions
- Other operational conditions affecting environmental exposure Use only on hard ground.
- Other operational conditions affecting worker exposure

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Avoid contact with the skin.

Avoid long-term or repeated skin contact.

- Other operational conditions affecting consumer exposure No special measures required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- Worker protection

Organisational protective measures

No special measures required.

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

Use product only in enclosed systems.

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Protective aloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use

(Contd. on page 13)

Page 13/15 Printing date 25.04.2020 Revision: 25.04.2020

Version number 17

Safety data sheet according to 1907/2006/EC, Article 31

Trade name: BODY AUTOCLEAR 493 2:1 MAT CLEAR CM-HS

(Contd. of page 12)

Environmental protection measures

Water

Do not allow to reach sewage system.

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Soil

Prevent contamination of soil.

The product is only processed over the concrete collecting basin.

· Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

- **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer

Not relevant for this Exposure Scenario.

This product is to be used by professional technitians only.

· Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

1 ()

(Contd. on page 14)

Trade name: BODY AUTOCLEAR 493 2:1 MAT CLEAR CM-HS

(Contd. of page 13)

Annex: Exposure scenario 2

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use According to directions for use.
- · Duration and frequency Frequency of use:
- · Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- · Physical state Fluid
- · Concentration of the substance in the mixture Raw material.
- · Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting worker exposure

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- Other operational conditions affecting consumer exposure No special measures required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- Worker protection
- · Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

Environmental protection measures

- Water Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.
- · **Soil** The product is only processed over the concrete collecting basin.
- · **Disposal measures** Ensure that waste is collected and contained.
- Disposal procedures Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- * Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- Consumer

This product is to be used by professional technitians only.

Not relevant for this Exposure Scenario.

(Contd. on page 15)

Page 15/15

Printing date 25.04.2020

Printing date 25.04.2020

according to 1907/2006/EC, Article 31

Revision: 25.04.2020 Version number 17

Trade name: BODY AUTOCLEAR 493 2:1 MAT CLEAR CM-HS

(Contd. of page 14)

· Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

GB