

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

| | | |
|-------------|----------------|---------------------------------|
| Version | Revision Date: | Date of last issue: 28.04.2020 |
| 2.1 GB / EN | 16.06.2021 | Date of first issue: 25.06.2019 |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Carsystem Spray

Product code : 127.978

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Body filler/stopper

Recommended restrictions
on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Vosschemie GmbH
Esinger Steinweg 50
25436 Uetersen
Germany

info@vosschemie.de

Telephone : 04122 717 0
Telefax : 04122 717158

Responsible Department : Laboratory

04122 717 0
sds@vosschemie.de

1.4 Emergency telephone number

Telephone : Giftinformationszentrum (GIZ)-Nord,
Göttingen, Deutschland
0551 19240

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

Version
2.1

GB / EN

Revision Date:
16.06.2021

Date of last issue: 28.04.2020
Date of first issue: 25.06.2019

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|--|---|
| Flammable liquids, Category 3 | H226: Flammable liquid and vapour. |
| Skin irritation, Category 2 | H315: Causes skin irritation. |
| Eye irritation, Category 2 | H319: Causes serious eye irritation. |
| Skin sensitisation, Category 1 | H317: May cause an allergic skin reaction. |
| Reproductive toxicity, Category 2 | H361d: Suspected of damaging the unborn child. |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system | H335: May cause respiratory irritation. |
| Specific target organ toxicity - repeated exposure, Category 1 | H372: Causes damage to organs through prolonged or repeated exposure. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H361d Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust / mist / vapours.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

Version
2.1

GB / EN

Revision Date:
16.06.2021

Date of last issue: 28.04.2020
Date of first issue: 25.06.2019

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

Hazardous components which must be listed on the label:

styrene
cobalt bis(2-ethylhexanoate)
maleic anhydride

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture
contains
Resin

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | Concentration (% w/w) |
|---------------|---|---|--------------------------|
| styrene | 100-42-5 202-851-5 601-026-00-0 | Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 | >= 20 - < 25 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

Version
2.1

GB / EN

Revision Date:
16.06.2021

Date of last issue: 28.04.2020
Date of first issue: 25.06.2019

| | | | |
|--|---|---|----------------------|
| | 01-2119457861-32 | Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H335 (Respiratory system) STOT RE 1; H372 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 | |
| Titanium dioxide | 13463-67-7 236-675-5 01-2119489379-17 | Carc. 2; H351 | $\geq 1 - < 10$ |
| cobalt bis(2-ethylhexanoate) | 136-52-7 205-250-6 01-2119524678-29 | Eye Irrit. 2; H319 Skin Sens. 1A; H317 Repr. 1B; H360F Aquatic Acute 1; H400 Aquatic Chronic 3; H412 | $\geq 0.025 - < 0.1$ |
| maleic anhydride | 108-31-6 203-571-6 607-096-00-9 01-2119472428-31 | Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1A; H317 STOT RE 1; H372 (Respiratory system) EUH071 specific concentration limit Skin Sens. 1A; H317 $\geq 0.001 \%$ | $\geq 0.001 - < 0.1$ |
| Substances with a workplace exposure limit : | | | |
| Talc | 14807-96-6 238-877-9 | | $\geq 10 - < 20$ |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
Move out of dangerous area.
Take off contaminated clothing and shoes immediately.
Do not leave the victim unattended.
Symptoms of poisoning may appear several hours later.
Show this safety data sheet to the doctor in attendance.

Protection of first-aiders : First Aid responders should pay attention to self-protection

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

| | | |
|-------------|----------------|---------------------------------|
| Version | Revision Date: | Date of last issue: 28.04.2020 |
| 2.1 GB / EN | 16.06.2021 | Date of first issue: 25.06.2019 |

- and use the recommended protective clothing
- If inhaled : Move to fresh air.
Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician immediately.
- In case of skin contact : Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Call a physician if irritation develops or persists.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Keep eye wide open while rinsing.
If easy to do, remove contact lens, if worn.
Consult a physician.
- If swallowed : Rinse mouth with water.
Do NOT induce vomiting.
Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation.
Suspected of damaging the unborn child.
Causes damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
Keep under medical supervision for at least 48 hours.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO₂)
Dry powder
Water spray jet
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.
- Hazardous combustion products : Hazardous decomposition products due to incomplete com-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

Version
2.1

GB / EN

Revision Date:
16.06.2021

Date of last issue: 28.04.2020
Date of first issue: 25.06.2019

from the application of this mixture.
Avoid inhalation of dust from sanding.

Advice on protection against fire and explosion : Vapours may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.

Further information on storage conditions : Keep away from heat and sources of ignition. Protect from moisture. Keep away from direct sunlight. Do not store at temperatures above 30 °C / 86 °F.

Advice on common storage : Incompatible with oxidizing agents.
Keep away from food and drink.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|--|------------|--|------------------------------------|------------|
| styrene | 100-42-5 | TWA | 100 ppm 430 mg/m ³ | GB EH40 |
| | | STEL | 250 ppm 1,080 mg/m ³ | GB EH40 |
| Barium sulphate | 7727-43-7 | TWA (inhalable dust) | 10 mg/m ³ | GB EH40 |
| | | TWA (Respirable dust) | 4 mg/m ³ | GB EH40 |
| Talc | 14807-96-6 | TWA (Respirable dust) | 1 mg/m ³ | GB EH40 |
| | | TWA (Respirable dust) | 0.1 mg/m ³ | 2004/37/EC |
| Further information: Carcinogens or mutagens | | | | |
| Titanium dioxide | 13463-67-7 | TWA (inhalable dust) | 10 mg/m ³ | GB EH40 |
| | | TWA (Respirable dust) | 4 mg/m ³ | GB EH40 |
| cobalt bis(2-ethylhexanoate) | 136-52-7 | TWA | 0.1 mg/m ³ (Cobalt) | GB EH40 |
| | | Further information: Capable of causing occupational asthma., Capable of causing cancer and/or heritable genetic damage. | | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

Version
2.1

GB / EN

Revision Date:
16.06.2021

Date of last issue: 28.04.2020
Date of first issue: 25.06.2019

| | | | | |
|--|----------|------|---------------------|---------|
| maleic anhydride | 108-31-6 | TWA | 1 mg/m ³ | GB EH40 |
| Further information: Capable of causing occupational asthma. | | | | |
| | | STEL | 3 mg/m ³ | GB EH40 |
| Further information: Capable of causing occupational asthma. | | | | |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|------------------------------|-----------|-----------------|---|--------------------------|
| styrene | Workers | Dermal | Long-term systemic effects, Chronic effects | 406 mg/kg bw/day |
| | Workers | Inhalation | Long-term systemic effects, Chronic effects | 85 mg/m ³ |
| | Workers | Inhalation | Acute systemic effects, Chronic effects | 289 mg/m ³ |
| | Workers | Inhalation | Acute local effects, Short-term exposure | 306 mg/m ³ |
| | Consumers | Oral | Long-term systemic effects, Chronic effects | 2.1 mg/kg bw/day |
| | Consumers | Dermal | Long-term systemic effects, Chronic effects | 343 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects, Chronic effects | 10.0 mg/m ³ |
| | Consumers | Inhalation | Acute systemic effects, Short-term exposure | 174.25 mg/m ³ |
| | Consumers | Inhalation | Acute local effects, Short-term exposure | 182.75 mg/m ³ |
| cobalt bis(2-ethylhexanoate) | Workers | Inhalation | Long-term local effects | 0.2351 mg/m ³ |
| | Consumers | Inhalation | Long-term local effects | 0.0037 mg/m ³ |
| | Consumers | Oral | Long-term systemic effects | 0.175 mg/kg bw/day |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|------------------------------|---------------------------|-------------------------------|
| styrene | Fresh water | 0.028 mg/l |
| | Marine water | 0.014 mg/l |
| | Fresh water sediment | 0.614 mg/kg dry weight (d.w.) |
| | Marine sediment | 0.307 mg/kg dry weight (d.w.) |
| | Soil | 0.2 mg/kg dry weight (d.w.) |
| | Sewage treatment plant | 5 mg/l |
| cobalt bis(2-ethylhexanoate) | Fresh water | 0.0006 mg/l |
| | Marine water | 0.00236 mg/l |
| | Sewage treatment plant | 0.37 mg/l |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

Version 2.1 GB / EN Revision Date: 16.06.2021 Date of last issue: 28.04.2020
Date of first issue: 25.06.2019

| | | |
|--|----------------------|------------------------------|
| | Fresh water sediment | 53.8 mg/kg dry weight (d.w.) |
| | Marine sediment | 69.8 mg/kg dry weight (d.w.) |
| | Soil | 10.9 mg/kg |

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : Fluorinated rubber
Break through time : > 480 min
Glove thickness : >= 0.4 mm
Directive : DIN EN 374
Protective index : Class 6

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection Butyl gloves are not suitable. Nitrile gloves are not suitable. Avoid natural rubber gloves.

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.
Long sleeved clothing

Respiratory protection : Apply technical measures to comply with the occupational exposure limits.
If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
Dry sanding, flame cutting and/or welding of the cured material will give rise to dust and/or hazardous fumes.
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).

Filter type : Combined particulates and organic vapour type (A-P)

Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.
Avoid contact with the skin and the eyes.
Use only with adequate ventilation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

| | | |
|-------------|----------------|---------------------------------|
| Version | Revision Date: | Date of last issue: 28.04.2020 |
| 2.1 GB / EN | 16.06.2021 | Date of first issue: 25.06.2019 |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|--|
| Physical state | : paste, liquid |
| Colour | : grey |
| Odour | : characteristic |
| Melting point/freezing point | : not determined |
| Melting point/range | : -30 °C Literary value styrene |
| Boiling point/boiling range | : 145 °C (1,013 hPa) Literary value styrene |
| Upper explosion limit / Upper flammability limit | : 6.1 %(V) Literary value styrene |
| Lower explosion limit / Lower flammability limit | : 1.1 %(V) Literary value styrene |
| Flash point | : 31 °C(1,013 hPa) Literary value styrene |
| Ignition temperature | : 490 °C (1,013 hPa) Literary value styrene |
| pH | : Not applicable substance/mixture is non-soluble (in water) |
| Viscosity | |
| Viscosity, dynamic | : not determined |
| Viscosity, kinematic | : not determined |
| Solubility(ies) | |
| Water solubility | : 0.32 g/l Literary value styrene (25 °C) |
| Partition coefficient: n-octanol/water | : No data available |
| Vapour pressure | : 6.67 hPa (20 °C) Literary value styrene |
| Density | : ca. 1.6 g/cm ³ (20 °C) |

9.2 Other information

| | |
|------------|---|
| Explosives | : Not explosive In use, may form flammable/explosive vapour-air mixture. |
|------------|---|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

Version

2.1

GB / EN

Revision Date:

16.06.2021

Date of last issue: 28.04.2020

Date of first issue: 25.06.2019

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Avoid radical-forming starting agents, peroxides and reactive metals.
Polymerisation can occur. Polymerisation is a highly exothermic reaction and may generate sufficient heat to cause thermal decomposition and/or rupture containers.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.

10.5 Incompatible materials

Materials to avoid : Strong acids and oxidizing agents
polymerisation initiators
Copper
Copper alloys
Brass

10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

styrene:

Acute oral toxicity : LD50 Oral (Rat): 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 11.8 mg/l
Exposure time: 4 h
Test atmosphere: vapour

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

Version 2.1 GB / EN Revision Date: 16.06.2021 Date of last issue: 28.04.2020
Date of first issue: 25.06.2019

Acute dermal toxicity : LD50 Dermal (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402

Titanium dioxide:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LD50 (Rat): > 6.8 mg/l
Exposure time: 4 h

cobalt bis(2-ethylhexanoate):

Acute oral toxicity : LD50 (Rat): 3,129 mg/kg
Method: OECD Test Guideline 425

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402

maleic anhydride:

Acute oral toxicity : LD50 Oral (Rat): 1,090 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 4.35 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): 2,620 mg/kg

Talc:

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity

Skin corrosion/irritation

Causes skin irritation.

Components:

styrene:

Species : Rabbit
Result : irritating

Titanium dioxide:

Remarks : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

styrene:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

| | | |
|---------|----------------|---------------------------------|
| Version | Revision Date: | Date of last issue: 28.04.2020 |
| 2.1 | 16.06.2021 | Date of first issue: 25.06.2019 |

Species : Rabbit
Result : irritating

Titanium dioxide:

Remarks : Dust contact with the eyes can lead to mechanical irritation.

cobalt bis(2-ethylhexanoate):

Result : Moderate eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

styrene:

Species : Guinea pig
Result : Does not cause skin sensitisation.

Titanium dioxide:

Remarks : No known sensitising effect.

cobalt bis(2-ethylhexanoate):

Exposure routes : Skin contact
Result : The product is a skin sensitiser, sub-category 1A.

maleic anhydride:

Result : The product is a skin sensitiser, sub-category 1A.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

styrene:

Reproductive toxicity - Assessment : Suspected of damaging the unborn child.

cobalt bis(2-ethylhexanoate):

Reproductive toxicity - Assessment : May damage fertility.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

Version
2.1

GB / EN

Revision Date:
16.06.2021

Date of last issue: 28.04.2020
Date of first issue: 25.06.2019

essment

STOT - single exposure

May cause respiratory irritation.

Components:

styrene:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Causes damage to organs (ear) through prolonged or repeated exposure if inhaled.

Components:

styrene:

Exposure routes : Inhalation
Target Organs : ear
Assessment : Causes damage to organs through prolonged or repeated exposure.

maleic anhydride:

Exposure routes : Inhalation
Target Organs : Respiratory system
Assessment : Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Components:

styrene:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

Version
2.1

GB / EN

Revision Date:
16.06.2021

Date of last issue: 28.04.2020
Date of first issue: 25.06.2019

SECTION 12: Ecological information

12.1 Toxicity

Components:

styrene:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 4.02 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 4.7 mg/l
aquatic invertebrates : Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 (Selenastrum capricornutum (green algae)): 4.9 mg/l
plants : Exposure time: 72 h

Toxicity to microorganisms : EC50 (Natural microorganism): ca. 500 mg/l
Method: OECD Test Guideline 209

Toxicity to fish (Chronic tox- : No data available:
icity)

Toxicity to daphnia and other : NOEC: 1,01 mg/l
aquatic invertebrates (Chron- : Exposure time: 21 d
ic toxicity) : Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Titanium dioxide:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
aquatic invertebrates : Exposure time: 48 h

cobalt bis(2-ethylhexanoate):

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 48 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia dubia (water flea)): 0.61 mg/l
aquatic invertebrates : Exposure time: 48 h

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): 0.144
plants : mg/l
End point: Growth rate
Exposure time: 72 h

Toxicity to microorganisms : EC10 (Bacteria): 3.73 mg/l
Exposure time: 3 h

Toxicity to fish (Chronic tox- : NOEC: 0.21 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

Version 2.1 GB / EN Revision Date: 16.06.2021 Date of last issue: 28.04.2020
Date of first issue: 25.06.2019

icity) End point: mortality
Exposure time: 34 d
Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.0608 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

maleic anhydride:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 75 mg/l
Exposure time: 96 h
Method: EPA-660/3-75-00

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 42.81 mg/l
End point: Immobilization
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 74.35 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

12.2 Persistence and degradability

Components:

styrene:

Biodegradability : Biodegradation: 70.9 %
Exposure time: 28 d
Readily biodegradable.

maleic anhydride:

Biodegradability : Biodegradation: > 90 %
Exposure time: 225 d
Method: OECD Test Guideline 301B

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

| | | |
|-------------|----------------|---------------------------------|
| Version | Revision Date: | Date of last issue: 28.04.2020 |
| 2.1 GB / EN | 16.06.2021 | Date of first issue: 25.06.2019 |

12.3 Bioaccumulative potential

Components:

styrene:

Partition coefficient: n-octanol/water : log Pow: 2.96 (25 °C)

maleic anhydride:

Partition coefficient: n-octanol/water : log Pow: -2.61 (20 °C)

12.4 Mobility in soil

Components:

styrene:

Distribution among environmental compartments : log Koc: 2.55

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
Dispose of in accordance with local regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

| | | | |
|---------|---------|----------------|---------------------------------|
| Version | | Revision Date: | Date of last issue: 28.04.2020 |
| 2.1 | GB / EN | 16.06.2021 | Date of first issue: 25.06.2019 |

Dispose of wastes in an approved waste disposal facility.
Send to a licensed waste management company.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Store containers and offer for recycling of material when in accordance with the local regulations.
Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:
07 02 08, other still bottoms and reaction residues

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1866
ADR : UN 1866
RID : UN 1866
IMDG : UN 1866
IATA : UN 1866

14.2 UN proper shipping name

ADN : RESIN SOLUTION
ADR : RESIN SOLUTION
RID : RESIN SOLUTION
IMDG : RESIN SOLUTION
IATA : Resin solution

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
ADR

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

| | | |
|---------|----------------|---------------------------------|
| Version | Revision Date: | Date of last issue: 28.04.2020 |
| 2.1 | 16.06.2021 | Date of first issue: 25.06.2019 |

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Class 3 - Flammable liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Class 3 - Flammable liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

Version 2.1 GB / EN Revision Date: 16.06.2021 Date of last issue: 28.04.2020
Date of first issue: 25.06.2019

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Directive 2004/42/EC
Volatile organic compounds (VOC) content: < 250 g/l
VOC content for the product in a ready to use condition.

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.
H302 : Harmful if swallowed.
H304 : May be fatal if swallowed and enters airways.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H334 : May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 : May cause respiratory irritation.
H351 : Suspected of causing cancer if inhaled.
H360F : May damage fertility.
H361d : Suspected of damaging the unborn child.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

Version 2.1 GB / EN Revision Date: 16.06.2021 Date of last issue: 28.04.2020
Date of first issue: 25.06.2019

- H372 : Causes damage to organs through prolonged or repeated exposure if inhaled.
H372 : Causes damage to organs through prolonged or repeated exposure.
H400 : Very toxic to aquatic life.
H412 : Harmful to aquatic life with long lasting effects.
EUH071 : Corrosive to the respiratory tract.

Full text of other abbreviations

- Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Carc. : Carcinogenicity
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity
Resp. Sens. : Respiratory sensitisation
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
2004/37/EC / TWA : Long term exposure limit
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECS - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem Spray

Version

2.1

GB / EN

Revision Date:

16.06.2021

Date of last issue: 28.04.2020

Date of first issue: 25.06.2019

of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

| | |
|---------------|-------|
| Flam. Liq. 3 | H226 |
| Skin Irrit. 2 | H315 |
| Eye Irrit. 2 | H319 |
| Skin Sens. 1 | H317 |
| Repr. 2 | H361d |
| STOT SE 3 | H335 |
| STOT RE 1 | H372 |

Classification procedure:

| |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.