

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem KS-800

Version		Revision Date:	Date of last issue: -
1.0	DE / EN	29.07.2022	Date of first issue: 29.07.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Carsystem KS-800

Product code : 126.095

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Solvent-borne coatings, Corrosion inhibitor
stance/Mixture

Recommended restrictions : Reserved for industrial and professional use.
on use Industrial use, professional use

1.3 Details of the supplier of the safety data sheet

Company : Vosschemie GmbH
Esinger Steinweg 50
25436 Uetersen
Germany
info@vosschemie.de

Telephone : 04122 717 0
Telefax : 04122 717158

Responsible Department : Laboratory

04122 717 0
sds@vosschemie.de

1.4 Emergency telephone

Telephone : Giftinformationszentrum (GIZ)-Nord,
Göttingen, Deutschland
0551 19240

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem KS-800

Version
1.0

DE / EN

Revision Date:
29.07.2022

Date of last issue: -
Date of first issue: 29.07.2022

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3

H226: Flammable liquid and vapor.

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms

:



Signal Word

:

Warning

Hazard Statements

:

H226 Flammable liquid and vapor.

H336 May cause drowsiness or dizziness.

Supplemental Hazard Statements

:

EUH066

Repeated exposure may cause skin dryness or cracking.

Precautionary Statements

:

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take action to prevent static discharges.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

Hazardous ingredients which must be listed on the label:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem KS-800

Version

1.0

DE / EN

Revision Date:

29.07.2022

Date of last issue: -

Date of first issue: 29.07.2022

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	64742-48-9 919-857-5 01-2119463258-33	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 EUH066	>= 25 - < 50
Sulfonic acids, petroleum, sodium salts	68608-26-4 271-781-5 01-2119527859-22	Eye Irrit. 2; H319	>= 3 - < 5
Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides	61789-77-3 263-087-6 01-2119486994-16	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 M-Factor (Acute aquatic toxicity): 1 Acute toxicity estimate Acute oral toxicity: 960 mg/kg	>= 0,1 - < 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem KS-800

Version
1.0

DE / EN

Revision Date:
29.07.2022

Date of last issue: -
Date of first issue: 29.07.2022

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
Move out of dangerous area.
Take off contaminated clothing and shoes immediately.
Do not leave the victim unattended.
Symptoms of poisoning may appear several hours later.
Show this material safety data sheet to the doctor in attendance.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Move to fresh air.
Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician immediately.
- In case of skin contact : Wash off immediately with soap and plenty of water.
Call a physician if irritation develops or persists.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Keep eye wide open while rinsing.
If easy to do, remove contact lens, if worn.
Consult a physician.
- If swallowed : Do NOT induce vomiting.
Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO₂)
Dry powder

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem KS-800

Version		Revision Date:	Date of last issue: -
1.0	DE / EN	29.07.2022	Date of first issue: 29.07.2022

Water spray jet
Alcohol-resistant foam

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

Hazardous combustion products : Hazardous decomposition products due to incomplete combustion
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire and/or explosion do not breathe fumes. In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear personal protective equipment.
Evacuate personnel to safe areas.
Ensure adequate ventilation, especially in confined areas.
Remove all sources of ignition.
Do not smoke.
Avoid contact with skin, eyes and clothing.
In the case of vapor formation use a respirator with an approved filter.

6.2 Environmental precautions

Environmental precautions : Prevent spreading over a wide area (e.g., by containment or oil barriers).
Do not flush into surface water or sanitary sewer system.
Local authorities should be advised if significant spillages cannot be contained.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem KS-800

Version

1.0

DE / EN

Revision Date:

29.07.2022

Date of last issue: -

Date of first issue: 29.07.2022

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
Do not flush with water.

Ventilate the area.

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Keep container closed when not in use.
Provide sufficient air exchange and/or exhaust in work rooms.
Wear personal protective equipment.

Use only in well-ventilated areas.

Advice on protection against fire and explosion : Vapors may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.

Further information on storage conditions : Keep away from heat and sources of ignition. Protect from moisture. Keep away from direct sunlight.

Advice on common storage : Keep away from food and drink.

Storage class (TRGS 510) : 3

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
----------------	---------	--------------------	--------------------------	-------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem KS-800

Version

1.0

DE / EN

Revision Date:

29.07.2022

Date of last issue: -

Date of first issue: 29.07.2022

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Workers	Inhalation	Long-term systemic effects	1500 mg/m3
	Workers	Skin contact	Long-term systemic effects	300 mg/m3
	Consumers	Inhalation	Long-term systemic effects	900 mg/m3
	Consumers	Skin contact	Long-term systemic effects	300 mg/m3
	Consumers	Oral	Long-term systemic effects	300 mg/m3
Sulfonic acids, petroleum, sodium salts	Workers	Inhalation	Long-term systemic effects	0,66 mg/m3
	Workers	Skin contact	Long-term systemic effects	3,33 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0,33 mg/m3
	Consumers	Skin contact	Long-term systemic effects	1,667 mg/kg
	Consumers	Oral	Long-term systemic effects	0,833 mg/kg
Quaternary ammonium compounds, dicocoo alkyldimethyl, chlorides	Workers	Inhalation	Long-term systemic effects	27 mg/m3
	Workers	Skin contact	Long-term systemic effects	12,75 mg/kg
	Consumers	Inhalation	Long-term systemic effects	8 mg/m3
	Consumers	Skin contact	Long-term systemic effects	7,65 mg/kg
	Consumers	Oral	Long-term systemic effects	2,3 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Sulfonic acids, petroleum, sodium salts	Fresh water	1 mg/l
	Sea water	1 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	723500000 mg/kg
	Sea sediment	723500000 mg/kg
	Soil	868700000 mg/kg
	Oral (Secondary Poisoning)	16,667 mg/kg
Quaternary ammonium compounds, dicocoo alkyldimethyl, chlorides	Fresh water	0,013 mg/l
	Sea water	0,013 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem KS-800

Version 1.0 DE / EN Revision Date: 29.07.2022 Date of last issue: -
Date of first issue: 29.07.2022

	Sewage treatment plant	1,2 mg/l
	Fresh water sediment	8,8 mg/kg
	Sea sediment	0,88 mg/kg
	Soil	7 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : >= 0,12 mm
Directive : DIN EN 374
Protective index : Class 6

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.
Long sleeved clothing

Respiratory protection : Apply technical measures to comply with the occupational exposure limits.
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).

Filter type : Organic vapor Type (A)

Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.
Avoid contact with the skin and the eyes.
Use only with adequate ventilation.

Environmental exposure controls

Soil : Avoid subsoil penetration.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : black

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem KS-800

Version		Revision Date:	Date of last issue: -
1.0	DE / EN	29.07.2022	Date of first issue: 29.07.2022

Odor	:	characteristic
Melting point/freezing point	:	not determined
Initial boiling point and boiling range	:	> 100 °C
Upper explosion limit / Upper flammability limit	:	7 %(V)
Lower explosion limit / Lower flammability limit	:	0,6 %(V)
Flash point	:	41 °C
Autoignition temperature	:	> 200 °C
pH	:	not determined substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	:	350 mPa.s (20 °C)
Viscosity, kinematic	:	not determined
Solubility(ies)		
Water solubility	:	immiscible
Partition coefficient: n-octanol/water	:	No data available
Vapor pressure	:	3 hPa (20 °C) 15 hPa (50 °C)
Density	:	0,86 g/cm ³ (20 °C)

9.2 Other information

Explosives	:	Not explosive In use, may form flammable/explosive vapor-air mixture.
Self-ignition	:	not auto-flammable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem KS-800

Version	Revision Date:	Date of last issue: -
1.0 DE / EN	29.07.2022	Date of first issue: 29.07.2022

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 9.300 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402

Sulfonic acids, petroleum, sodium salts:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 1,9 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg
Method: OECD Test Guideline 402

Carsystem KS-800

Version

1.0

DE / EN

Revision Date:

29.07.2022

Date of last issue: -

Date of first issue: 29.07.2022

Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides:

Acute oral toxicity : LD50 Oral (Rat): 960 mg/kg
Method: OECD Test Guideline 401

Acute toxicity estimate: 960 mg/kg
Method: Calculation method

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:**

Assessment : Repeated exposure may cause skin dryness or cracking.

Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides:

Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Sulfonic acids, petroleum, sodium salts:**

Result : Moderate eye irritation

Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides:

Result : Irreversible effects on the eye

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:**

Carcinogenicity - Assessment : Carcinogenicity classification not possible from current data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem KS-800

Version
1.0

DE / EN

Revision Date:
29.07.2022

Date of last issue: -
Date of first issue: 29.07.2022

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause drowsiness or dizziness.

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 1.000 mg/l
aquatic invertebrates
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000
plants
mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem KS-800

Version	Revision Date:	Date of last issue: -
1.0	29.07.2022	Date of first issue: 29.07.2022

DE / EN

Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR: 0,131 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 0,23 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Sulfonic acids, petroleum, sodium salts:

Toxicity to fish : LL50 (Cyprinodon variegatus (sheepshead minnow)): > 10.000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1.000 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 1.000 mg/l
Exposure time: 72 h

EC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC50 (Bacteria): >= 3.200 - 5.000 mg/l
Exposure time: 8 h
Method: OECD Test Guideline 209

Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 0,26 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Acartia tonsa): 0,295 mg/l
End point: mortality
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 0,386 mg/l
End point: Growth rate
Exposure time: 72 h
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem KS-800

Version		Revision Date:	Date of last issue: -
1.0	DE / EN	29.07.2022	Date of first issue: 29.07.2022

M-Factor (Acute aquatic toxicity) : 1

Toxicity to fish (Chronic toxicity) : NOEC: ca. 0,23 mg/l
Exposure time: 35 d
Species: Pimephales promelas (fathead minnow)

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Biodegradability : Result: Readily biodegradable.

Sulfonic acids, petroleum, sodium salts:

Biodegradability : Result: Not biodegradable

Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 20 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

12.3 Bioaccumulative potential

Components:

Sulfonic acids, petroleum, sodium salts:

Partition coefficient: n-octanol/water : log Pow: 22,12 (25 °C)

Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides:

Partition coefficient: n-octanol/water : log Pow: 4,8 (25 °C)

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem KS-800

Version

1.0

DE / EN

Revision Date:

29.07.2022

Date of last issue: -

Date of first issue: 29.07.2022

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
Dispose of in accordance with local regulations.
Send to a licensed waste management company.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1139
ADR : UN 1139
RID : UN 1139
IMDG : UN 1139
IATA : UN 1139

14.2 UN proper shipping name

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem KS-800

Version		Revision Date:	Date of last issue: -
1.0	DE / EN	29.07.2022	Date of first issue: 29.07.2022

ADN	:	COATING SOLUTION (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics)
ADR	:	COATING SOLUTION (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics)
RID	:	COATING SOLUTION (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics)
IMDG	:	COATING SOLUTION (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics)
IATA	:	Coating solution (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics)

14.3 Transport hazard class(es)

ADN	:	3
ADR	:	3
RID	:	3
IMDG	:	3
IATA	:	3

14.4 Packing group

ADN	
Packing group	: III
Classification Code	: F1
Labels	: 3
ADR	
Packing group	: III
Classification Code	: F1
Labels	: 3
Tunnel restriction code	: (E)
RID	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 33
Labels	: 3
IMDG	
Packing group	: III
Labels	: 3
EmS Code	: F-E, <u>S-E</u>
IATA (Cargo)	
Packing instruction (cargo aircraft)	: 366
Packing instruction (LQ)	: Y344

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem KS-800

Version	Revision Date:	Date of last issue: -
1.0 DE / EN	29.07.2022	Date of first issue: 29.07.2022

Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Seveso III: Directive 2012/18/EU of the Euro- P5c FLAMMABLE LIQUIDS

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem KS-800

Version	Revision Date:	Date of last issue: -
1.0 DE / EN	29.07.2022	Date of first issue: 29.07.2022

European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Water hazard class (Germany)	: WGK 1 slightly water endangering Classification according to AwSV, Annex 1 (5.2)
Volatile organic compounds	: Directive 2004/42/EC Volatile organic compounds (VOC) content: < 430 g/l VOC content for the product in a ready to use condition.

15.2 Chemical Safety Assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapor.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H314	: Causes severe skin burns and eye damage.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H336	: May cause drowsiness or dizziness.
H400	: Very toxic to aquatic life.
H411	: Toxic to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Corr.	: Skin corrosion
STOT SE	: Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration as-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Carsystem KS-800

Version

1.0

DE / EN

Revision Date:

29.07.2022

Date of last issue: -

Date of first issue: 29.07.2022

sociated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3

H226

STOT SE 3

H336

Classification procedure:

Based on product data or assessment

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN