

CUSTOMISING TAPE

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Bulldog Homegrown Customising Tape uses a thermally stabilised PVC backing with a rubber-based pressure sensitive adhesive. The product has 8 strips of pre-cut fine line masking tape - allowing a multitude of curved patterns to be created when customising. It is highly flexible, easy to curve and will hold and cleanly remove from surfaces in temperatures up to 150°C/300°F for at least 1 hour. After demasking, it will leave no residue and a sharp, clean separation line.

SHELF LIFE

One year from date of receipt by customer when stored at 20°C ±10°C (68°F ±18°F) and 60% relative humidity.

PHYSICAL PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Carrier	PVC
Adhesive	Rubber
Colour	Green
Thickness	150µm / 0.150mm (±0.03mm)
Width	8 x 1.5mm (1/16") strips giving total width of 12mm.
Length	10m (±0.1m)

PERFORMANCE PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Peel Adhesion (to steel)	2.6N/cm (±0.8)
Elongation at Break	>100%
Tensile Strength	>22N/cm
Temperature Resistance	up to 150°C (300°F) for 1 hour

PRODUCT CONSTRUCTION



BULLDOG ABRASIVES

No. 4 Andries Street South, Wynberg, Johannesburg, 2090

Tel: +27 (0) 11 786 5991

Email: sales@bulldogabrasives.co.za

Website: www.bulldogabrasives.co.za