

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

**VOSSCHEMIE**

## Carsystem Multi Flow

Version  
1.0

DE / EN

Revision Date:  
24.09.2025

Date of last issue: -  
Date of first issue: 24.09.2025

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Carsystem Multi Flow  
Product code : 160.363

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Body filler/stopper  
Recommended restrictions on use : Industrial use, professional use

#### 1.3 Details of the supplier of the safety data sheet

Company : Vosschemie GmbH  
Esinger Steinweg 50  
25436 Uetersen  
Germany  
info@vosschemie.de

Telephone : 04122 717 0  
Telefax : 04122 717158

**Responsible Department** : Laboratory  
04122 717 0  
sds@vosschemie.de

#### 1.4 Emergency telephone

Telephone : Giftinformationszentrum (GIZ)-Nord,  
Göttingen, Deutschland  
0551 19240

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

VOSSCHEMIE

## Carsystem Multi Flow

Version  
1.0

DE / EN

Revision Date:  
24.09.2025

Date of last issue: -  
Date of first issue: 24.09.2025

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - repeated exposure, Category 1	H372: Causes damage to organs through prolonged or repeated exposure.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H361d Suspected of damaging the unborn child.  
H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**  
P201 Obtain special instructions before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe dust / mist / vapours.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

VOSSCHEMIE

## Carsystem Multi Flow

Version  
1.0

DE / EN

Revision Date:  
24.09.2025

Date of last issue: -  
Date of first issue: 24.09.2025

attention.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

**Hazardous ingredients which must be listed on the label:**

styrene  
maleic anhydride

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Resin  
Mixture

**Components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
styrene	100-42-5 202-851-5 601-026-00-0 01-2119457861-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H335 (Respiratory system) STOT RE 1; H372 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 10 - < 20

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

VOSSCHEMIE

## Carsystem Multi Flow

Version  
1.0

DE / EN

Revision Date:  
24.09.2025

Date of last issue: -  
Date of first issue: 24.09.2025

		Acute toxicity estimate  Acute inhalation toxicity (vapor): 11,8 mg/l	
maleic anhydride	108-31-6 203-571-6 607-096-00-9 01-2119472428-31	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1A; H317 STOT RE 1; H372 (Respiratory system) EUH071  specific concentration limit Skin Sens. 1A; H317 => 0,001 %  Acute toxicity estimate  Acute oral toxicity: 1.090 mg/kg	=> 0,001 - < 0,1
Substances with a workplace exposure limit :			
Talc	14807-96-6 238-877-9		=> 20 - < 30

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

General advice

- : In the case of accident or if you feel unwell, seek medical advice immediately.
- Move out of dangerous area.
- Take off contaminated clothing and shoes immediately.
- Do not leave the victim unattended.
- Symptoms of poisoning may appear several hours later.
- Show this material safety data sheet to the doctor in attendance.

Protection of first-aiders

- : First Aid responders should pay attention to self-protection and use the recommended protective clothing

If inhaled

- : Move to fresh air.
- Keep patient warm and at rest.
- If breathing is irregular or stopped, administer artificial respiration.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

VOSSCHEMIE

## Carsystem Multi Flow

Version 1.0	DE / EN	Revision Date: 24.09.2025	Date of last issue: - Date of first issue: 24.09.2025
----------------	---------	------------------------------	--

tion.  
Call a physician immediately.

In case of skin contact : Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.  
Call a physician if irritation develops or persists.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Keep eye wide open while rinsing.  
If easy to do, remove contact lens, if worn.  
Consult a physician.

If swallowed : Rinse mouth with water.  
Do NOT induce vomiting.  
Call a physician immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Suspected of damaging the unborn child.  
Causes damage to organs through prolonged or repeated exposure.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.  
Keep under medical supervision for at least 48 hours.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2)  
Dry powder  
Water spray jet  
Alcohol-resistant foam

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

Hazardous combustion products : Hazardous decomposition products due to incomplete combustion  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

VOSSCHEMIE

## Carsystem Multi Flow

Version  
1.0

DE / EN

Revision Date:  
24.09.2025

Date of last issue: -  
Date of first issue: 24.09.2025

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

Further information : Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear personal protective equipment. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Remove all sources of ignition. Do not smoke. Avoid contact with skin, eyes and clothing. Sweep up to prevent slipping hazard. In the case of vapor formation use a respirator with an approved filter.

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. Do not flush with water.

### 6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Keep container closed when not in use. Provide sufficient air exchange and/or exhaust in work rooms. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

# SAFETY DATA SHEET

VOSSCHEMIE

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Carsystem Multi Flow

Version 1.0	DE / EN	Revision Date: 24.09.2025	Date of last issue: - Date of first issue: 24.09.2025
----------------	---------	------------------------------	--

Advice on protection against fire and explosion : Vapors may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.

Further information on storage conditions : Keep away from heat and sources of ignition. Protect from moisture. Keep away from direct sunlight. Do not store at temperatures above 30 °C / 86 °F.

Advice on common storage : Incompatible with oxidizing agents. Keep away from food and drink.

Storage class (TRGS 510) : 3

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Talc	14807-96-6	AGW (Inhalable fraction)	10 mg/m3	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		TWA (Respirable dust)	0,1 mg/m3	2004/37/EC
	Further information: Carcinogens or mutagens			
		BM (Alveolar dust fraction)	0,5 mg/m3	DE TRGS 527
styrene	100-42-5	AGW	20 ppm 86 mg/m3	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK	20 ppm	DE DFG MAK

# SAFETY DATA SHEET

VOSSCHEMIE

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Carsystem Multi Flow

Version  
1.0

DE / EN

Revision Date:  
24.09.2025

Date of last issue: -  
Date of first issue: 24.09.2025

			86 mg/m3	
	Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
Barium sulphate	7727-43-7	AGW (Inhalable fraction)	10 mg/m3	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK (measured as the alveolate fraction)	0,3 mg/m3	DE DFG MAK
	Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
		MAK (inhalable fraction)	4 mg/m3	DE DFG MAK
	Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
Titanium dioxide	13463-67-7	AGW (Inhalable fraction)	10 mg/m3 (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m3 (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		BM (Alveolar dust fraction)	0,5 mg/m3	DE TRGS 527
		MAK (measured as the alveolate fraction)	0,3 mg/m3	DE DFG MAK
	Peak-limit category: 8; II			
	Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
maleic anhydride	108-31-6	AGW (Vapour and aerosols)	0,02 ppm 0,081 mg/m3	DE TRGS 900
	Peak-limit category: 1; =2.5=(I)			
	Further information: In well-found cases also a momentary value can be es-			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

VOSSCHEMIE

## Carsystem Multi Flow

Version  
1.0

DE / EN

Revision Date:  
24.09.2025

Date of last issue: -  
Date of first issue: 24.09.2025

	Established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin and respiratory system			
		Mow	0,05 ppm 0,2 mg/m3	DE DFG MAK
	Further information: Danger of sensitization of the airways and the skin, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
		MAK	0,02 ppm 0,081 mg/m3	DE DFG MAK
	Further information: Danger of sensitization of the airways and the skin, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
styrene	100-42-5	mandelic acid + phenylglyoxylic acid: 600 mg/g creatinine (Urine)	In case of long-term exposure: after more than one shift, Immediately after exposure or after working hours	TRGS 903
		mandelic acid plus phenylglyoxylic acid: 600 mg/g creatinine (Urine)	end of shift, for long-term exposures after several previous shifts, Immediately after exposition or after working hours	DE DFG BAT

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Routes of exposure	Potential health effects	Value
styrene	Workers	Dermal	Long-term systemic effects, Chronic effects	406 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects, Chronic effects	85 mg/m3
	Workers	Inhalation	Acute systemic effects, Chronic effects	289 mg/m3
	Workers	Inhalation	Acute local effects, Short-term exposure	306 mg/m3
	Consumers	Oral	Long-term systemic effects, Chronic effects	2,1 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects, Chronic effects	343 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects, Chronic effects	10,2 mg/m3

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

VOSSCHEMIE

## Carsystem Multi Flow

Version  
1.0

DE / EN

Revision Date:  
24.09.2025

Date of last issue: -  
Date of first issue: 24.09.2025

			fects	
	Consumers	Inhalation	Acute systemic effects, Short-term exposure	174,25 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects, Short-term exposure	182,75 mg/m <sup>3</sup>
maleic anhydride	Workers	Inhalation	Long-term systemic effects	0,081 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	0,2 mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
styrene	Fresh water	0,028 mg/l
	Sea water	0,014 mg/l
	Fresh water sediment	0,614 mg/kg dry weight (d.w.)
	Sea sediment	0,307 mg/kg dry weight (d.w.)
	Soil	0,2 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	5 mg/l
maleic anhydride	Fresh water	0,038 mg/l
	Sea water	0,004 mg/l
	Fresh water sediment	0,296 mg/kg dry weight (d.w.)
	Sea sediment	0,03 mg/kg dry weight (d.w.)
	Soil	0,037 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	44,6 mg/l

## 8.2 Exposure controls

### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Hand protection  
Guideline : Equipment should conform to EN 374

Material : PVA  
Break through time : > 480 min  
Glove thickness : 0,2 - 0,3 mm

Material : Fluorinated rubber  
Break through time : > 480 min  
Glove thickness : >= 0,4 mm

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

VOSSCHEMIE

## Carsystem Multi Flow

Version 1.0	DE / EN	Revision Date: 24.09.2025	Date of last issue: - Date of first issue: 24.09.2025
----------------	---------	------------------------------	--

to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection  
Avoid neoprene and natural rubber gloves.

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.  
Long sleeved clothing

Respiratory protection : Apply technical measures to comply with the occupational exposure limits.  
If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.  
Dry sanding, flame cutting and/or welding of the cured material will give rise to dust and/or hazardous fumes.  
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).

Filter type : Combined particulates and organic vapor type (A-P)

Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
Avoid contact with the skin and the eyes.  
Use only with adequate ventilation.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : paste

Color : blue

Odor : characteristic

Melting point/ range : -30 °C  
Literary value styrene

Boiling point/boiling range : 145 °C (1.013 hPa)  
Literary value styrene

Flammability : Flammable

Upper explosion limit / Upper flammability limit : 6,1 %(V)  
Literary value styrene

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

VOSSCHEMIE

## Carsystem Multi Flow

Version  
1.0

DE / EN

Revision Date:  
24.09.2025

Date of last issue: -  
Date of first issue: 24.09.2025

---

Lower explosion limit / Lower flammability limit	:	1,1 % (V) Literary value styrene
Flash point	:	31 °C (1.013 hPa) Literary value styrene
Autoignition temperature	:	490 °C (1.013 hPa) Literary value styrene
Decomposition temperature	:	No data available
pH	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	:	not determined
Viscosity, kinematic	:	not determined
Solubility(ies)		
Water solubility	:	0,32 g/l (25 °C) Literary value styrene
Partition coefficient: n-octanol/water	:	log Pow: 2,96 (25 °C) Literary value styrene
Vapor pressure	:	6,67 hPa (20 °C) Literary value styrene
Density	:	ca. 1,2 g/cm3 (20 °C)
Relative vapor density	:	No data available

### 9.2 Other information

Explosives	:	Not explosive In use, may form flammable/explosive vapour-air mixture.
------------	---	---

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if used as directed.

**Carsystem Multi Flow**Version  
1.0

DE / EN

Revision Date:  
24.09.2025Date of last issue: -  
Date of first issue: 24.09.2025**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Avoid radical-forming starting agents, peroxides and reactive metals.  
Polymerization can occur. Polymerization is a highly exothermic reaction and may generate sufficient heat to cause thermal decomposition and/or rupture containers.

**10.4 Conditions to avoid**

Conditions to avoid : Heat, flames and sparks.  
Strong sunlight for prolonged periods.

**10.5 Incompatible materials**

Materials to avoid : Strong acids and oxidizing agents  
polymerization initiators  
Copper  
Copper alloys  
Brass

**10.6 Hazardous decomposition products**

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Not classified due to lack of data.

**Product:**

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

**Components:****styrene:**

Acute oral toxicity : LD50 Oral (Rat): 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 11,8 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 402

**maleic anhydride:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

VOSSCHEMIE

## Carsystem Multi Flow

Version 1.0	DE / EN	Revision Date: 24.09.2025	Date of last issue: - Date of first issue: 24.09.2025
----------------	---------	------------------------------	--

Acute oral toxicity	:	LD50 Oral (Rat): 1.090 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC50 (Rat): > 4,35 mg/l Exposure time: 1 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 2.620 mg/kg

### Talc:

Acute oral toxicity	:	LD50 Oral (Rat): 5.000 mg/kg Method: OECD Test Guideline 423
Acute inhalation toxicity	:	Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	:	LD50 Dermal (Rat): > 2.000 mg/kg Method: OECD Test Guideline 402

### Skin corrosion/irritation

Causes skin irritation.

### Components:

#### styrene:

Species	:	Rabbit
Result	:	irritating

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Components:

#### styrene:

Species	:	Rabbit
Result	:	irritating

### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### Respiratory sensitization

Not classified due to lack of data.

### Components:

#### styrene:

Species	:	Guinea pig
Result	:	Does not cause skin sensitization.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

VOSSCHEMIE

## Carsystem Multi Flow

Version  
1.0 DE / EN

Revision Date:  
24.09.2025

Date of last issue: -  
Date of first issue: 24.09.2025

---

### **maleic anhydride:**

Result : The product is a skin sensitizer, sub-category 1A.

### **Germ cell mutagenicity**

Not classified due to lack of data.

### **Carcinogenicity**

Not classified due to lack of data.

### **Reproductive toxicity**

Suspected of damaging the unborn child.

### **Components:**

#### **styrene:**

Reproductive toxicity - Assessment : Suspected of damaging the unborn child., Some evidence of adverse effects on development, based on animal experiments.

### **STOT-single exposure**

Not classified due to lack of data.

### **Components:**

#### **styrene:**

Assessment : May cause respiratory irritation.

### **STOT-repeated exposure**

Causes damage to organs (hearing organs) through prolonged or repeated exposure if inhaled.

### **Components:**

#### **styrene:**

Routes of exposure : Inhalation  
Target Organs : hearing organs  
Assessment : Causes damage to organs through prolonged or repeated exposure.

### **maleic anhydride:**

Routes of exposure : Inhalation  
Target Organs : Respiratory system  
Assessment : Causes damage to organs through prolonged or repeated exposure.

### **Aspiration toxicity**

Not classified due to lack of data.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

VOSSCHEMIE

## Carsystem Multi Flow

Version  
1.0 DE / EN

Revision Date:  
24.09.2025

Date of last issue: -  
Date of first issue: 24.09.2025

### Components:

#### **styrene:**

May be fatal if swallowed and enters airways.

### 11.2 Information on other hazards

#### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### **styrene:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 4,02 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4,7 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 4,9 mg/l  
Exposure time: 72 h

EC10 (Selenastrum capricornutum (green algae)): 0,28 mg/l  
Exposure time: 96 h

Toxicity to microorganisms : EC50 (Natural microorganism): ca. 500 mg/l  
Method: OECD Test Guideline 209

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,01 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

#### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

#### **maleic anhydride:**

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 75 mg/l  
Exposure time: 96 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

VOSSCHEMIE

## Carsystem Multi Flow

Version 1.0	DE / EN	Revision Date: 24.09.2025	Date of last issue: - Date of first issue: 24.09.2025
----------------	---------	------------------------------	--

Method: EPA-660/3-75-00

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 37,9 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 65,78 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)

### Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

## 12.2 Persistence and degradability

### Components:

#### **styrene:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 70,9 %  
Exposure time: 28 d

#### **maleic anhydride:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: > 90 %  
Exposure time: 225 d  
Method: OECD Test Guideline 301B

## 12.3 Bioaccumulative potential

### Components:

#### **styrene:**

Partition coefficient: n-octanol/water : log Pow: 2,96 (25 °C)

#### **maleic anhydride:**

Partition coefficient: n-octanol/water : log Pow: -2,61 (20 °C)

#### **Talc:**

Partition coefficient: n-octanol/water : log Pow: -9,4 (25 °C)  
pH: 7

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

VOSSCHEMIE

## Carsystem Multi Flow

Version 1.0	DE / EN	Revision Date: 24.09.2025	Date of last issue: - Date of first issue: 24.09.2025
----------------	---------	------------------------------	--

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information

: No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product

: Do not dispose of with domestic refuse.  
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
Dispose of in accordance with local regulations.  
Dispose of wastes in an approved waste disposal facility.  
Send to a licensed waste management company.

Contaminated packaging

: Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Store containers and offer for recycling of material when in accordance with the local regulations.  
Packaging that is not properly emptied must be disposed of as the unused product.  
Dispose of in accordance with local regulations.

Waste Code

: The following Waste Codes are only suggestions:  
07 02 08, other still bottoms and reaction residues

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

VOSSCHEMIE

## Carsystem Multi Flow

Version  
1.0

DE / EN

Revision Date:  
24.09.2025

Date of last issue: -  
Date of first issue: 24.09.2025

### SECTION 14: Transport information

#### 14.1 UN number or ID number

<b>ADN</b>	:	UN 1866
<b>ADR</b>	:	UN 1866
<b>RID</b>	:	UN 1866
<b>IMDG</b>	:	UN 1866
<b>IATA</b>	:	UN 1866

#### 14.2 UN proper shipping name

<b>ADN</b>	:	RESIN SOLUTION
<b>ADR</b>	:	RESIN SOLUTION
<b>RID</b>	:	RESIN SOLUTION
<b>IMDG</b>	:	RESIN SOLUTION
<b>IATA</b>	:	Resin solution

#### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	:	3
<b>ADR</b>	:	3
<b>RID</b>	:	3
<b>IMDG</b>	:	3
<b>IATA</b>	:	3

#### 14.4 Packing group

<b>ADN</b>
Packing group
Classification Code
Hazard Identification Number
Labels
<b>ADR</b>
Packing group
Classification Code
Hazard Identification Number
Labels
Tunnel restriction code
<b>RID</b>
Packing group
Classification Code
Hazard Identification Number
Labels

# SAFETY DATA SHEET

VOSSCHEMIE

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Carsystem Multi Flow

Version  
1.0

DE / EN

Revision Date:  
24.09.2025

Date of last issue: -  
Date of first issue: 24.09.2025

### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADN

Environmentally hazardous : no

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

VOSSCHEMIE

## Carsystem Multi Flow

Version  
1.0

DE / EN

Revision Date:  
24.09.2025

Date of last issue: -  
Date of first issue: 24.09.2025

---

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2004/42/EC  
Volatile organic compounds (VOC) content: < 250 g/l  
VOC content for the product in a ready to use condition.

### Other regulations:

The product is subject to the supply restrictions of the Ordinance on the Prohibition of Chemicals.

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

## 15.2 Chemical Safety Assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

---

## SECTION 16: Other information

### Full text of H-Statements

- H226 : Flammable liquid and vapor.
- H302 : Harmful if swallowed.
- H304 : May be fatal if swallowed and enters airways.
- H314 : Causes severe skin burns and eye damage.
- H315 : Causes skin irritation.
- H317 : May cause an allergic skin reaction.
- H318 : Causes serious eye damage.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

VOSSCHEMIE

## Carsystem Multi Flow

Version 1.0	DE / EN	Revision Date: 24.09.2025	Date of last issue: - Date of first issue: 24.09.2025
----------------	---------	------------------------------	--

H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H361d	: Suspected of damaging the unborn child.
H372	: Causes damage to organs through prolonged or repeated exposure if inhaled.
H372	: Causes damage to organs through prolonged or repeated exposure.
H412	: Harmful to aquatic life with long lasting effects.
EUH071	: Corrosive to the respiratory tract.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Resp. Sens.	: Respiratory sensitization
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitization
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2004/37/EC	: Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens, mutagens or reprotoxic substances at work - Annex III
DE DFG BAT	: Germany. MAK BAT Annex XIII
DE DFG MAK	: Germany. MAK BAT Annex IIa
DE TRGS 527	: Germany. TRGS 527 - Activities with nanomaterials
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903	: c - Biological limit values
2004/37/EC / TWA	: Long term exposure limit
DE DFG MAK / Mow	: Momentary value
DE DFG MAK / MAK	: MAK value
DE TRGS 527 / BM	: Assessment scale
DE TRGS 900 / AGW	: Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships car-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

**VOSSCHEMIE**

## Carsystem Multi Flow

Version 1.0	Revision Date: 24.09.2025	Date of last issue: - Date of first issue: 24.09.2025
----------------	------------------------------	--

ryng Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECL - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Repr. 2	H361d
STOT RE 1	H372

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BPO-Härter rot

Version  
2.6

DE / EN

Revision Date:  
30.09.2025

Date of last issue: 16.04.2025  
Date of first issue: 11.07.2022

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : BPO-Härter rot  
Product code : 150.284

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Curing chemical  
Recommended restrictions on use : Industrial use, professional use, public use

#### 1.3 Details of the supplier of the safety data sheet

Company : A.Förster & Co.KG  
Esinger Steinweg 50  
25436 Uetersen  
Germany  
info@foerster-co.de

Telephone : 04122-3682

**Responsible Department** : Laboratory  
04122-3682  
info@foerster-co.de

#### 1.4 Emergency telephone

Telephone : Giftinformationszentrum (GIZ)-Nord,  
Göttingen, Deutschland  
0551 19240

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

**A. Forster**  
& CO.KG

## BPO-Härter rot

Version  
2.6 DE / EN

Revision Date:  
30.09.2025

Date of last issue: 16.04.2025  
Date of first issue: 11.07.2022

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Organic peroxides, Type E	H242: Heating may cause a fire.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Category 1	H410: Very toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H242 Heating may cause a fire.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H410 Very toxic to aquatic life with long lasting effects.

Precautionary Statements : P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

#### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances /combustible materials.  
P234 Keep only in original packaging.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BPO-Härter rot

Version  
2.6

DE / EN

Revision Date:  
30.09.2025

Date of last issue: 16.04.2025  
Date of first issue: 11.07.2022

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P314 Get medical advice/ attention if you feel unwell.

### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.  
P410 Protect from sunlight.

### Disposal:

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

### Hazardous ingredients which must be listed on the label:

dibenzoyl peroxide

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Mixture  
contains  
Organic Peroxide

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
dibenzoyl peroxide	94-36-0 202-327-6 617-008-00-0 01-2119511472-50	Org. Perox. B; H241 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute)	>= 45 - <= 52

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BPO-Härter rot

Version 2.6	Revision Date: 30.09.2025	Date of last issue: 16.04.2025 Date of first issue: 11.07.2022
----------------	------------------------------	---

		aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10	
ethanediol	107-21-1 203-473-3 603-027-00-1 01-2119456816-28	Acute Tox. 4; H302 STOT RE 2; H373 (Kidney)	>= 1 - < 10

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
Move out of dangerous area.  
Take off contaminated clothing and shoes immediately.  
Show this material safety data sheet to the doctor in attendance.  
First aider needs to protect himself.

If inhaled : Move to fresh air.  
Get medical attention.

In case of skin contact : Wash off immediately with soap and plenty of water.  
Call a physician if irritation persists.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Keep eye wide open while rinsing.  
Remove contact lenses.  
Consult a physician.

If swallowed : Rinse mouth with water.  
Do NOT induce vomiting.  
Call a physician immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.  
Causes serious eye irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BPO-Härter rot

Version 2.6	Revision Date: 30.09.2025	Date of last issue: 16.04.2025 Date of first issue: 11.07.2022
----------------	------------------------------	---

Dry powder  
Water spray jet  
Alcohol-resistant foam

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Hazardous decomposition products formed under fire conditions.

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus and protective suit.

Further information : Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear personal protective equipment.  
Evacuate personnel to safe areas.  
Ensure adequate ventilation, especially in confined areas.  
Remove all sources of ignition.  
Do not smoke.  
Avoid contact with skin, eyes and clothing.  
In the case of vapor formation use a respirator with an approved filter.

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.  
Do not flush with water.

### 6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BPO-Härter rot

Version  
2.6

DE / EN

Revision Date:  
30.09.2025

Date of last issue: 16.04.2025  
Date of first issue: 11.07.2022

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Technical measures	: Ensure that eyewash stations and safety showers are close to the workstation location.
Advice on safe handling	: Use only with adequate ventilation. Provide sufficient air exchange and/or exhaust in work rooms. Wear personal protective equipment. Keep away from heat and sources of ignition. Handle and open container with care. Keep container tightly closed and dry. Never return unused material to storage receptacle. Risk of decomposition. Prevent contamination with readily oxidizable materials and polymerization accelerators. Avoid inhalation of vapor or mist. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid release to the environment.
Advice on protection against fire and explosion	: Normal measures for preventive fire protection. Keep away from open flames, hot surfaces and sources of ignition. Keep away from direct sunlight. Avoid shock and friction. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	: Store in original container. Avoid letting the product become dry. Keep containers tightly closed in a cool, well-ventilated place. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.
Advice on common storage	: Keep away from food, drink and animal feedingstuffs. Keep away from reducing agents. Incompatible with acids and bases. Heavy metal compounds
Storage class (TRGS 510)	: 5.2
Recommended storage temperature	: 5 - 25 °C

#### 7.3 Specific end use(s)

Specific use(s)	: No data available The rules which cover amongst other things the requirement for ventilation, protective clothing, personal protective equipment etc. can be obtained from the National Occupational Health and Safety Board.
-----------------	--

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BPO-Härter rot

Version  
2.6

DE / EN

Revision Date:  
30.09.2025

Date of last issue: 16.04.2025  
Date of first issue: 11.07.2022

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
dibenzoyl peroxide	94-36-0	AGW (Inhalable fraction)	5 mg/m3	DE TRGS 900	
		Peak-limit category: 1;(I)			
		MAK (measured as the alveolate fraction)	1 mg/m3	DE DFG MAK	
		Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
		MAK (inhalable fraction)	4 mg/m3	DE DFG MAK	
		Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
ethanediol	107-21-1	STEL	40 ppm 104 mg/m3	2000/39/EC	
		Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	20 ppm 52 mg/m3	2000/39/EC	
		Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW (Vapour and aerosols)	10 ppm 26 mg/m3	DE TRGS 900	
		Peak-limit category: 2;(I)			
		Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK	10 ppm 26 mg/m3	DE DFG MAK	
		Further information: Danger of absorption through the skin, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			

##### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Routes of exposure	Potential health effects	Value
dibenzoyl peroxide	Workers	Inhalation	Long-term systemic effects	39 mg/m3
	Workers	Dermal	Long-term systemic effects	13,3 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
ethanediol	Workers	Inhalation	Long-term local effects	35 mg/m3
	Workers	Dermal	Long-term systemic effects	106 mg/kg bw/day

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BPO-Härter rot

Version 2.6	Revision Date: 30.09.2025	Date of last issue: 16.04.2025 Date of first issue: 11.07.2022
----------------	------------------------------	---

	Consumers	Inhalation	Long-term local effects	7 mg/m3
	Consumers	Dermal	Long-term systemic effects	53 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
dibenzoyl peroxide	Fresh water	0,00002 mg/l
	Intermittent use/release	0,000602 mg/l
	Sea water	0,000002 mg/l
	Fresh water sediment	0,0127 mg/kg dry weight (d.w.)
	Sea sediment	0,00127 mg/kg dry weight (d.w.)
	Soil	0,0025 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	0,35 mg/l

## 8.2 Exposure controls

### Personal protective equipment

Eye/face protection	: Safety glasses with side-shields conforming to EN166
Hand protection	
Material	: Neoprene gloves
Material	: Nitrile rubber
Break through time	: > 30 min
Glove thickness	: >= 0,14 mm
Guideline	: DIN EN 374
Protective index	: Class 2
Remarks	: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.
Skin and body protection	: Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres. Long sleeved clothing
Respiratory protection	: Apply technical measures to comply with the occupational exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Filter type	: Combined particulates and organic vapor type (A-P)
Protective measures	: When using do not eat, drink or smoke.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BPO-Härter rot

Version  
2.6

DE / EN

Revision Date:  
30.09.2025

Date of last issue: 16.04.2025  
Date of first issue: 11.07.2022

Ensure that eye flushing systems and safety showers are located close to the working place.  
Avoid contact with the skin and the eyes.  
Use only with adequate ventilation.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	:	paste
Color	:	red
Odor	:	characteristic
Odor Threshold	:	not determined
Melting point/ range	:	0 °C
Boiling point/boiling range	:	Not applicable
Upper explosion limit / Upper flammability limit	:	Not applicable
Lower explosion limit / Lower flammability limit	:	Not applicable
Flash point	:	Not applicable, Decomposition
Autoignition temperature	:	Not applicable
Self-Accelerating decomposition temperature (SADT)	:	50 °C
pH	:	4 - 5 (20 °C)
Viscosity		
Viscosity, dynamic	:	not determined

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BPO-Härter rot

Version  
2.6

DE / EN

Revision Date:  
30.09.2025

Date of last issue: 16.04.2025  
Date of first issue: 11.07.2022

Viscosity, kinematic : not determined

Solubility(ies)  
Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapor pressure : 23 hPa  
(for a component of this mixture)

Density : 1,15 - 1,25 g/cm<sup>3</sup> (20 °C)

Relative vapor density : not determined

### 9.2 Other information

Oxidizing properties : Organic peroxide

Sustains combustion

Organic peroxides : Peroxide content: 50 %  
The substance or mixture is an organic peroxide classified as type E.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if used as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Risk of decomposition.  
Reacts violently in contact with acids, amines, driers, polymerization accelerators and easily oxidized materials.

### 10.4 Conditions to avoid

Conditions to avoid : Do not expose to temperatures above: > 25 °C  
Extremes of temperature and direct sunlight.  
Keep away from heat and sources of ignition.  
Contact with incompatible substances can cause decomposition at or below SADT.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BPO-Härter rot

Version  
2.6

DE / EN

Revision Date:  
30.09.2025

Date of last issue: 16.04.2025  
Date of first issue: 11.07.2022

### 10.5 Incompatible materials

Materials to avoid : Accelerators, strong acids and bases, heavy metals and heavy metal salts, reducing agents

### 10.6 Hazardous decomposition products

Irritant, caustic, flammable, noxious/toxic gases and vapours can develop in the case of fire and decomposition

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified due to lack of data.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

#### Components:

##### **dibenzoyl peroxide:**

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg  
Acute inhalation toxicity : LC0 (Rat): > 24,3 mg/l  
Exposure time: 4 h

##### **ethanediol:**

Acute oral toxicity : LD50 (Rat): 7.712 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 2,5 mg/l  
Exposure time: 6 h  
Test atmosphere: dust/mist  
Acute dermal toxicity : LD50 Dermal (Mouse): > 3.500 mg/kg

#### **Skin corrosion/irritation**

Not classified due to lack of data.

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Respiratory or skin sensitization**

##### **Skin sensitization**

May cause an allergic skin reaction.

##### **Respiratory sensitization**

Not classified due to lack of data.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BPO-Härter rot

Version  
2.6 DE / EN

Revision Date:  
30.09.2025

Date of last issue: 16.04.2025  
Date of first issue: 11.07.2022

---

### **Germ cell mutagenicity**

Not classified due to lack of data.

### **Carcinogenicity**

Not classified due to lack of data.

### **Reproductive toxicity**

Not classified due to lack of data.

### **STOT-single exposure**

Not classified due to lack of data.

### **STOT-repeated exposure**

Not classified due to lack of data.

### **Components:**

#### **ethanediol:**

Routes of exposure : Oral  
Target Organs : Kidney  
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

### **Aspiration toxicity**

Not classified due to lack of data.

### **Components:**

#### **ethanediol:**

No aspiration toxicity classification

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### **Components:**

#### **dibenzoyl peroxide:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0,0602 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BPO-Härter rot

Version 2.6	DE / EN	Revision Date: 30.09.2025	Date of last issue: 16.04.2025 Date of first issue: 11.07.2022
----------------	---------	------------------------------	---

NOEC (Oncorhynchus mykiss (rainbow trout)): 0,0316 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,11 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

NOEC (Daphnia magna (Water flea)): 0,076 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (microalgae)): 0,0711 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,02 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 10

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10: 0,001 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 10

### ethanediol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 72.860 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEC (algae): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: 15.380 mg/l  
Exposure time: 7 d  
Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 8.590 mg/l  
Exposure time: 7 d  
Species: Ceriodaphnia dubia (water flea)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BPO-Härter rot

Version 2.6	Revision Date: 30.09.2025	Date of last issue: 16.04.2025 Date of first issue: 11.07.2022
----------------	------------------------------	---

### 12.2 Persistence and degradability

#### Components:

##### **dibenzoyl peroxide:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 71 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

##### **ethanediol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 90 - 100 %  
Exposure time: 10 d  
Method: OECD Test Guideline 301A

### 12.3 Bioaccumulative potential

#### Components:

##### **dibenzoyl peroxide:**

Partition coefficient: n-octanol/water : log Pow: 3,2 (20 °C)

##### **ethanediol:**

Partition coefficient: n-octanol/water : log Pow: -1,36 (25 °C)

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BPO-Härter rot

Version 2.6	DE / EN	Revision Date: 30.09.2025	Date of last issue: 16.04.2025 Date of first issue: 11.07.2022
----------------	---------	------------------------------	---

### 12.7 Other adverse effects

#### Product:

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product	: Do not mix waste streams during collection. Do not dispose of with domestic refuse. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Dispose of in accordance with local regulations.
Contaminated packaging	: Packaging that is not properly emptied must be disposed of as the unused product. Dispose of in accordance with local regulations.
Waste Code	: The following Waste Codes are only suggestions: 16 05 06, laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals 16 09 03, peroxides, for example hydrogen peroxide

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

<b>ADN</b>	: UN 3108
<b>ADR</b>	: UN 3108
<b>RID</b>	: UN 3108
<b>IMDG</b>	: UN 3108
<b>IATA</b>	: UN 3108

### 14.2 UN proper shipping name

<b>ADN</b>	: ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide)
<b>ADR</b>	: ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide)
<b>RID</b>	: ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide)
<b>IMDG</b>	: ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide)
<b>IATA</b>	: Organic peroxide type E, solid (dibenzoyl peroxide)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BPO-Härter rot

Version  
2.6

DE / EN

Revision Date:  
30.09.2025

Date of last issue: 16.04.2025  
Date of first issue: 11.07.2022

### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	: 5.2	
<b>ADR</b>	: 5.2	
<b>RID</b>	: 5.2	
<b>IMDG</b>	: 5.2	
<b>IATA</b>	: 5.2	HEAT

### 14.4 Packing group

#### **ADN**

Packing group : Not assigned by regulation  
Classification Code : P1  
Labels : 5.2

#### **ADR**

Packing group : Not assigned by regulation  
Classification Code : P1  
Labels : 5.2  
Tunnel restriction code : (D)

#### **RID**

Packing group : Not assigned by regulation  
Classification Code : P1  
Hazard Identification Number : 539  
Labels : 5.2

#### **IMDG**

Packing group : Not assigned by regulation  
Labels : 5.2  
EmS Code : F-J, S-R

#### **IATA (Cargo)**

Packing instruction (cargo aircraft) : 570  
Packing group : Not assigned by regulation  
Labels : Organic Peroxides, Keep Away From Heat

#### **IATA (Passenger)**

Packing instruction (passenger aircraft) : 570  
Packing group : Not assigned by regulation  
Labels : Organic Peroxides, Keep Away From Heat

### 14.5 Environmental hazards

#### **ADN**

Environmentally hazardous : yes

#### **ADR**

Environmentally hazardous : yes

#### **RID**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BPO-Härter rot

Version  
2.6

DE / EN

Revision Date:  
30.09.2025

Date of last issue: 16.04.2025  
Date of first issue: 11.07.2022

Environmentally hazardous : no

**IMDG**

Marine pollutant : yes

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

: Conditions of restriction for the following entries should be considered: Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).

: Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer

: Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast)

: Not applicable

REACH - List of substances subject to authorisation (Annex XIV)

: Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P6b

SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

E1

ENVIRONMENTAL HAZARDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

#### Other regulations:

BG-Merkblatt M001 beachten (German regulatory requirements)  
according to DGUV Regulation 13 (previously BGV B4) - Organic Peroxides

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BPO-Härter rot

Version  
2.6 DE / EN

Revision Date:  
30.09.2025

Date of last issue: 16.04.2025  
Date of first issue: 11.07.2022

Hazard group: OP II

§ 5Abs. 4b : Derogation according to the Ordinance on the Prohibition of Chemicals (ChemVerbotsV)

The product is subject to the supply restrictions of the Ordinance on the Prohibition of Chemicals.

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical Safety Assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

## SECTION 16: Other information

### Full text of H-Statements

H241	: Heating may cause a fire or explosion.
H302	: Harmful if swallowed.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H373	: May cause damage to organs through prolonged or repeated exposure if swallowed.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Irrit.	: Eye irritation
Org. Perox.	: Organic peroxides
Skin Sens.	: Skin sensitization
STOT RE	: Specific target organ toxicity - repeated exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
DE DFG MAK	: Germany. MAK BAT Annex IIa
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
DE DFG MAK / MAK	: MAK value
DE TRGS 900 / AGW	: Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regula-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BPO-Härter rot

Version  
2.6

DE / EN

Revision Date:  
30.09.2025

Date of last issue: 16.04.2025  
Date of first issue: 11.07.2022

tion (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Org. Perox. E	H242
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN